

Smash 115.

SPECIFICATION		SMASH115
Engine Type	4-Stroke, Single Cylinder, SOHC, 2-Valve	
Bore and Stroke	51.0mm x 55.2mm	
Max Power	6.4kw / 8,000rpm	
Max Torque	9.0 N-m / 4,000 rpm	
Displacement	112.8cc	
Compression Ratio	9.5:1	
Fuel System	Carburetor	
Cooling System	Air-Cooled	
Lubrication	Wet Sump	
Starting	Electric / Kick	
Ignition System	CDI	
Transmission Type	4-speed Constant Mesh	
Clutch Type [Primary]	NA	
Suspension	Front	Telescopic, coil spring, oil damped
	Rear	Swing arm type, coil spring, oil damped
Tire Size	Front	70/90 - 17 M / C 38P
	Rear	80/90 - 17 M / C 44P
Brakes	Front	Drum (Spoke) / Disc (Mags)
	Rear	Drum
Length x Width x Height	1,930mm x 655mm x 1,040mm	
Wheelbase	1,240mm	
Ground/Road Clearance	130mm	
Curb Mass	99kg	
Fuel Tank Capacity	4.3L	

COLOR VARIANTS

SPOKES



New Celebration Red



Pearl Mirage White



New Titan Black

FEATURES



Sports Watch Inspired Speedometer with Gear Position Indicator



Large 8-Liter Underseat Compartment



Stable Magwheels



Large Diameter Muffler with Large Oxidation Catalyst and The Suzuki Environmental Pair System



Smooth Riding Suspension.



Comfortable Seat Design and Height.



Theft Preventive Magnetic Key Shutter.



Visible Rear Combination Lamp with Multi-Polygon Reflector and Taillight.

CONNECT WITH US



www.suzuki.com.ph



[facebook.com/SuzukiBikersFed](https://www.facebook.com/SuzukiBikersFed)



follow us @suzukibikers



customercare@suzuki.com.ph



Way of Life!

SUZUKI PHILIPPINES, INCORPORATED
126 Progress Avenue, Carmelray Industrial Park 1
CarmelTown, Cantubang, Calamba City 4026 Laguna
Tel : (02) 462-5000 Fax : (02) 462-5040 to 41



Smash 115.



Suzuki Engine



The Smash 115 offers upgraded performance in terms of power and fuel efficiency.



GSXR-Inspired

The leading-edge design is made to uplift every riders character as it cuts through air with its enhanced aerodynamic styling.



Diamond-Type Chassis

With key specifications of 26 caster angle, 64mm trail and 1,240mm wheelbase, Smash 115 delivers a user-friendly combination of smooth handling and comfortable straight-line running in various riding conditions.